



**Tender enquiry no. ADMIN/Tender/Wardrobes in Type Iv & V/1/2014**  
**Corrigendum for Wardrobes tender**

A corrigendum for schedule of quantity which is mentioned in Page no. 26 to 28 in tender document. The detailed amendment are as below table:

**SCHEDULE OF QUANTITY**

Name of Work: Providing Wardrobes and miscellaneous works in Type IV & V at AIIMS Residential Complex Raipur

S no	Description of item	Qty	Unit	Rate	Amount
1	Providing and fixing BWP grade ply confirming to IS: 303 in wardrobes, drawers, cabinets and shelves etc. Exposed edges shall be provided with minimum 5 mm thick teak wood lipping wherever required with suitable nails and adhesive. Wherever required, Ply shall be fixed to the wall with suitable size SS screws with rawl plugs, all complete as per direction of Engineer - in - charge.				
	(i) 18 mm thick	1679.00	Sqm		
	(ii) 12 mm thick	445.00	Sqm		
2	Providing and fixing stainless steel butt hinges with screws of suitable size for shutters of cupboards, wardrobes, cabinets & shelves etc, all complete, as per direction of Engineer - In - Charge.				
	(i) 100 mm x (20mm x 20mm) x 1.5 mm thick	810.00	Each		
	(ii) 75mm x (20mm x 20 mm) x 1.5 mm thick	2430.00	Each		
3	Providing and fixing of Mica laminates of approved shade and make/manufacture with approved adhesive on plywood in wardrobes, shelves, drawers and cupboard etc. all complete as per direction of Engineer - In - Charge.				
	(i) 0.8 mm Thick	3439.00	Sqm		
4	Providing and fixing stainless steel telescopic drawer slide (similar to EBCO item no : STDS35 ) with necessary screws and all complete. As per direction of Engineer - In - Charge.				
	(i) 350 mm long	135.00	Set		

S no	Description of item	Qty	Unit	Rate	Amount
5	Providing and fixing special quality bright finished brass cupboard/ ward robe four levers locks of 'ebco' or equivalent make including necessary screws etc. complete. (a) 65 mm	135.00	Each		
6	Providing and fixing magnetic catcher of approved quality in cupboard / wardrobe shutters, including fixing with necessary screws and etc. complete. (i) Double strip (horizontal type)	66.00	Each		
7	Providing and fixing foldable SS handles for drawer of size 75 mm with screws, all complete as per direction of the Engineer - In - Charge.	135	Each		
8	Providing and fixing of SS handle for cupboards of size 125 mm with screws and all complete, as per direction of Engineer - In - Charge.	1080	Each		
9	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z section/ appropriate two track section for sliding windows and other sections of approved make conforming to IS :733 and IS :1285, fixed clips, or with expansion hold fasteners including necessary filling up of gaps at junctions, at top, bottom and sides with required PVC/neoprene frlt etc. Aluminium sections shall be smooth, rust free straight, mitred and jointed mechanically wherever required including cleat angle, aluminium snap beading for glazing /panelling, CP. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer - in- charge. (Glazing and panneling to be paid separately);				
(a)	For fixed portion	3112.56	kg		
	(i) Powder coated aluminum (minimum thickness of polyester power coating 50 micron)				
(b)	For shutters of doors, windows & ventilators including providing and fixing of fittings wherever required including the cost of PVC / neoprene gasket required (fittings shall be paid for separately).				
	(i) Powder coated aluminum (minimum thickness of polyester power coating 50 micron)	1465.08	kg		
10	Providing and fixing fly proof galvanized MS wire gauge to windows using wire gauge with average width of aperture 104mm in both directions with wire of dia 0.63 mm and	588.56	Sqm		

S no	Description of item	Qty	Unit	Rate	Amount
	necessary clips/beading all complete.				
11	Providing and fixing wash basin with CI brackets, 15 mm CP brass pillar tap, 32 mm CP . Brass waste of standard pattern, including paiting of fittings and brackets, cutting and making good the walls wherever require :				
	(i) White vitreous china wash basin size 450 x 300 mm.	24	Each		
12	Providing and fixing cast iron 100 mm dia pipe as per IS :3989.	80	Metre		
13	Providing and fixing M.S holder bat clamps of approved design to cetrifugally cast spun iron/ cast iron (spun)pipe embedded in and including cement concrete blocks 10 x 10 x 10 cm of 1:2:4 mix (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) including cost of cutting holes and making good the walls etc.				
	(i) For 100 mm dia. Pipe	50	Each		
14	Providing and fixing bend of required degree with access door, insertion rubber washer 3 mm thick, bolts and nuts complete.				
	(i) 100 mm Sand cast iron S&S as per IS - 1729	3	Each		
15	Providing and fixing GI pipes (medium class) complete with GI fittings and clamps, including cutting and making good the walls etc.. Exposed on wall. (i) 15mm dia nominal bore.	120	Metre		
16	Concealed GI pipe including paiting with anti corrosive bitumastic paint chases and making good the wall. 15mm dia nominal bore.	70	Metre		
17	Making connection of GI distribution branch with GI main of follwing sizes by providing and fixing tee, including cutting and threading the pipe etc. complete. (i) 25 to 40 nominal bore.	3	Each		
18	Providing and fixing ball valve brass of approved quality, high or low pressure, with plastic floats complete. (i) 15 mm nominal bore.	3	Each		
19	Providing and fixing CP brass angle valve for Basin mixer and geyser points of approved quality confirming to IS: 8931 (i) 15 mm nominal bore.	24	Each		
20	Providing lead caulked joints to sand cast iron / cetifugally cast spun iron pipe and fittings of diametre. (i) 100 mm pipe.	24	Each		
21	Providing and fixing collar for 100 mm sand cast iron S & S as per IS : 3989.	5	Each		

S no	Description of item	Qty	Unit	Rate	Amount
22	Painting sand cast iron / centrifugally cast (spun) iron soil waste pipes and fittings with two coats of synthetic enamel paint of any colour such as chocolate gray or buff etc. Over a coat of primer of approved quality of new work . (i) 100 mm dia pipe.	80	Metre		
23	Providing and fixing square mouth SW gully trap class SP-I complete with CI grating brick masonry chamber with water tight CI Cover with frame of 300 x 300 mm size (inside) the weight of the cover to be not less than 4.5 kg and frame to be not less than 2.7 kg as per standard design with fly ash bricks of class designation 75.	3	Each		
24	Making connection of drain or sewer line with existing manhole including breaking in to and making good the walls, floor with cement concrete 1:2:4 mix (1 cement: 2 coarse sand:4 graded stone stone aggregate 20 mm nominal size) cement plastered on both sides with cement mortar 1:3 (1 cement:3 coarse sand), finished with a floating coat of neat cement and making necessary channels of the drain etc.. complete. (i) For pipe 100 to 250 mm dia.	3	Each		
25	Steel work welded in built up tubular ( round, square or rectangular hollow tubes etc.) trusses etc., including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer and two coats of paint, including welding complete.				
	(i) Hot finished welded type tubes.	200	Kg		
26	Making holes in brick wall of required size for 50 to 100 mm dia drainage pipe and repairing inc. plastering and painting similar to existing finish after completion of piping work.	24	Each		
27	Providing and fixing single equal plain junction of required degree with access door, insertion rubber washer 3 mm thick, bolts and nuts complete.				
	(i) 100 mm x 100 mm x 100 mm Sand cast iron S&S as per IS - 1729	24	Each		
28	Providing and fixing uplasticised PVC connection pipe with brass unions :				
	(i) 15 mm nominal bore	24	Each		
29	Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved quality) complete with 6 mm thick hard board ground fixed to wooden cleats with C.P. brass screws and washers complete.	24	Each		

<b>S no</b>	<b>Description of item</b>	<b>Qty</b>	<b>Unit</b>	<b>Rate</b>	<b>Amount</b>
30	Providing and fixing PTMT liquid soap container 109 mm wide, 125 mm high and 112 mm distance from wall of standard shape with bracket of the same materials with snap fittings of approved quality and colour, weighing not less than 105 gms.	24	Each		
31	Providing and fixing PTMT towel ring trapezoidal shape 215 mm long, 200 mm wide with minimum distances of 37 mm from wall face with concealed fittings arrangement of approved quality and colour, weighing not less than 88 gms.	24	Each		

**Administrative Officer  
AIIMS, Raipur**