Notice Inviting Tender for

"Multipara & Neonatal Multipara Monitor"

At

All India Institute of Medical Sciences, Raipur

No	DME Stage	Start Date & Time
1	NIT No.	Admin/Tender/ Multipara & Neonatal
1.		Multipara Monitor / 1 / 2014
2.	NIT issue date	11-09-2014
3.	Pre bid Meeting	30-09-2014 at 12:30 PM
4.	Last Date of submission	13-10-2014 at 03:00 PM



All India Institute of Medical Sciences, Raipur Tatibandh, Raipur – 492099, Chhattisgarh

Tele: 0771-2573777, email: admin@aiimsraipur.edu.in Website: www.aiimsraipur.edu.in, www.tenders.gov.in

<u>Chapter I- Instruction to bidders</u> <u>Notice Inviting Tender</u> "Multipara & Neonatal Multipara Monitor"

All India Institute of Medical Sciences, Raipur, Chhattisgarh, an apex healthcare institute being established by Parliament of India under aegis of Ministry of Health & Family Welfare, Government of India, invites sealed Tenders for supply & installation of the following item(s) at the institute. You are requested to quote your best offer along with the complete detail of specifications, terms & conditions.

Schedule	Name of the Items required to be purchased	Quantity tendered for
А.	Multipara Monitor (High End)	14
B.	Neonatal Multipara Monitor (High End)	02
C.	Multipara Monitor	08

- Interested parties may send their tender in sealed cover addressed to the Administrative Officer, All India Institute of Medical Sciences, Tatibandh, Raipur superscripted with tender number and complete in all respects latest by 13-10-2014 up to 3:00 pm. The Quotations will be opened on the same day at 04.00 PM in the Committee Hall, Medical College Building, All India Institute of Medical Sciences, Raipur. The tenders received after the scheduled date and time will be rejected out rightly.
- 2. The tender is in <u>two- bid</u> system i.e. Technical Bid & Financial Bid .The technical bid will be opened on the designated date by the Purchase Committee. The financial bid containing the rate of various item(s) will be opened on a suitable date, to be intimated later by the Purchase Committee in respect of those who qualify the terms and conditions of the technical bid.
- 3. The bidder should seal the technical bid and the financial bid in separate covers super scribed "Technical bid for Tender for Multipara & Neonatal Multipara Monitor" and "Financial Bid for Tender for Multipara & Neonatal Multipara Monitor". Both Sealed Envelopes should be kept in a main/ bigger envelope super scribed as "Tender for Multipara & Neonatal Multipara Monitor". The 'Technical Bid" will be analyzed and 'Financial Bid' of only those firms who are found eligible in 'Technical Bid' will be opened in due course and the eligible firms would be intimated there of accordingly.

Issue Date	:	11-09-2014				
Pre bid Meeting	:	30-09-2014 a	30-09-2014 at 12:30 PM			
Last date and time of receipt of tender	:	13-10-2014 at 04:00 PM				
Amount of Earnest	:	Schedule A	₹ 4,20,000/- (Rupees Four Lakhs &			
Money Deposit (EMD)			Twenty Thousand)			
		Schedule B	₹ 60,000/- (Rupees Sixty Thousand)			
		Schedule C	₹ 1,20,000/- (Rupees One Lakhs & Forty			
			Four Thousand)			
Tender Cost	:	₹ 5000/- (Ru	₹ 5000/- (Rupees Five Thousand Only)			
Date & time of opening of tender	:	13-10-2014a	13-10-2014at 04:00 PM			
Venue	:	Administrat	Administrative Office, AIIMS, Tatibandh, Raipur-492099			

Schedule of Tender

4. Tender document may be downloaded from this Institute's official website http://www.aiimsraipur.edu.in, www.tenders.gov.in and the tenderer shall deposit a separate Nationalized Bank DD/ Pay Order in favour of "All India Institute of Medical Sciences, Raipur" worth ₹ 5,000/- along with tender Document (Technical Bid) & EMD of requisite amount. The tenders submitted without tender cost or without EMD shall be liable to be rejected summarily. The cost of the bid document is non-refundable.

Administrative Officer AIIMS, Raipur

Chapter-II- Conditions of Contract

General Terms and Conditions

<u>Subject:-</u> Notice Inviting Tender for Multipara & Neonatal Multipara Monitor for All India Institute of Medical Sciences, Raipur

1. Earnest Money:

Earnest money by means of a Nationalized Bank DD/BG/FDR of

- ₹ 4,20,000/- (Rupees Four Lakh & Twenty Thousand) for Schedule- A
- ₹ 60,000/- (Rupees Sixty Thousand) for Schedule- B
- ₹ 1,20,000/- (Rupees One Lakh & Twenty Thousand only) for Schedule- C

Should be enclosed with the quotation (Technical Bid). It is also clarified that the quotations received without earnest money will be summarily rejected. The DD/BG/FDR may be prepared in the name of "All India Institute of Medical Sciences, Raipur".

- a) No request for transfer of any pervious deposit of earnest money or security deposit or payment of any pending bill held by the ministry in respect of any previous work will be entertained.
- b) Tenderer shall not be permitted to withdraw his offer or modify the terms and conditions thereof. In case the tenderer fail to observe and comply with stipulations made herein or backs out after quoting the rates, the aforesaid amount of earnest money will be forfeited.
- c) Tenders without Earnest Money or Tender cost will be summarily rejected.
- d) No claim shall lie against the AIIMS in respect of erosion in the value or interest on the amount of EMD.

2. <u>Preparation and Submission of Tender:</u>

• The tender should be submitted in two parts i.e. Technical Bid and Financial Bid. The Technical Bid and the Financial Bid should be sealed by the bidder in two separate covers "Technical Bid for Tender for Multipara & Neonatal Multipara Monitor" and "Financial Bid for Tender for Multipara & Neonatal Multipara Monitor". Both Sealed Envelopes should be kept in a main/ bigger envelope super scribed as "Tender for Multipara & Neonatal Multipara Monitor"

- Tender shall be rejected if the copy of sales tax registration certificate (now called as VAT) is not furnished. Firm shall furnish a certificate on their firm's letterhead stating that up to date returns have been filed and there are no dues with the concerned department. Firm will also submit the copies of such returns (latest) submitted to the department of trade & taxes.
- Hand written quotations shall be accepted at bidder's risk. In case of any discrepancy in the figures, the rate mentioned in words will only be considered.
- All the equipment quoted should be supplied along with the original catalogue with detailed data sheet.

3. Signing of Tender:

All the duly filled/completed pages of the tender should be given serial /page number on each page and signed. The individual signing the tender or other documents connected with contract must specify whether he sign as:

- a) A sole proprietor of the concern or constituted attorney of such sole proprietor;
- b) A partner of the firm, if it is a partnership firm in which case he must have authority to execute the contracts on behalf of the firm and to refer to arbitration disputes concerning the business of the partnership either by virtue of the partnership agreement or by a power of attorney duly executed by the partners of the firm.
- c) Director or a principal officer duly authorized by the Board of Directors of the Company, if it is a company.

<u>N.B.</u>

- i. In case of partnership firms, a copy of the partnership agreement, or general power of attorney duly attested by a Notary Public, should be furnished on stamped paper duly sworn or affirmed by all the partners admitting execution of the partnership agreement or the general power of attorney. The attested copy of the certificate of registration of firm should also be enclosed along with the tender.
- ii. In the case of partnerships firm, where no authority to refer disputes concerning the business of partnership firm has been conferred on any partner, the tender and all other related document must be signed by all partners of the firm.
- iii. A person signing the tender form or any document forming part of the tender on behalf of another person should have an authority to bind such other person and if, on enquiry it appears that the person so signing had no authority to do so, AIIMS, Raipur may without prejudice, cancel the contract and hold the signatory liable for all costs, consequences and damages under the civil and criminal remedies available.
- iv. The tenderer should sign and affix his firm's stamp at each page of the tender and all its annexure as the acceptance of the offer made by tenderer will be deemed as a contract and no separate formal contract will be drawn. NO PAGE SHOULD BE REMOVED/ DETACHED FROM THIS NOTICE INVITING TENDER.

4. **Opening of Tender**

The tenderer is at liberty to present either him or authorize not more than one representative to be present at the opening of the tender. The representative present at the opening of the tender on behalf of the tenderer should bring with him a letter of authority from the tenderer and proof of identification

5. <u>Validity of the bids:</u>

The bids shall be valid for a period of 180 days from the date of opening of the tender. This has to be so specified by the tenderer in the commercial bid which may be extended if required.

6. <u>Right of acceptance:</u>

AIIMS, Raipur reserve the right to accept or reject any or all tenders /quotations without assigning any reason there of and also does not bind itself to accept the lowest quotation or any tender. AIIMS, Raipur also reserves the rights to accept all the equipment/instruments in the given tender or only part of it in any given schedule without assigning any reason. Any failure on the part of the contractor to observe the prescribed procedure and any attempt to canvass for the work will prejudice the contractor's quotation or any tender.

7. <u>Performance Security:</u>

The successful tenderer will be required to furnish a Performance Security Deposit of 10% of tender amount in the form of Demand Draft, Fixed Deposit Receipt or Bank Guarantee from any Nationalized Bank duly pledged in the name of the "All India Institute of Medical Sciences, Raipur". The security deposit can be forfeited by order of this Institute in the event of any breach or negligence or non–observance of any condition of contract or for unsatisfactory performance or non–observance of any condition of the contract.

Performance Security shall be submitted in the form of Demand Draft, Bank Guarantee or Fixed Deposit Receipt issued by any Nationalized Bank. Performance Security will valid till 60 days after completion of contractual obligations (including warranty period, **if applicable**) under the contract.

After completion of warranty period a fresh BG/DD/FDR of 10% of CMC cost will be submitted by the supplier for performance security against CMC validity of this new BG/DD/FDR will be 60 days beyond CMC period. After submission of new security deposit, old security deposit will be released.

8. Delivery & Installation:

The successful bidders should strictly adhere to the following delivery schedule supply, installation & Commissioning should be effected within 4 to 6 weeks from the date of supply order and this clause should be strictly adhere to failing which administrative action as deemed fit under rules will be taken against the defaulter.

9. Inspecting, Testing and Quality control

- i. The purchaser or its nominal representative will inspect and test the ordered goods and the related services to confirm their conformity to the contract specification and other quality control details incorporated.
- ii. The Purchaser reserves the right for stage inspection during manufacturing process, pre-dispatch inspection or post-delivery inspection. The Purchaser as deemed fit shall resort to all these inspection or may waive off any of the inspection.
- iii. Stage Inspection: The Supplier shall offer semi-finished product without paint for stage inspection supported with invoice & test report of major raw material as per relevant specification standards.
- iv. Before resorting to Bulk Manufacture, the supplier shall offer/send the prototype/actual-finished sample for approval by the Inspector. The approval of Samples shall be in respect of workmanship and finishing and shall be without prejudice to the rights of purchaser/user to get random testing of items during predispatch inspection or form the actual lot offered. In the event of the failure of the supplier to deliver the sample by the date specified in the contact or any other date agreed by the purchaser or in the event of rejection of the sample second time, the purchaser shall be entitled to cancel the contract and purchase the stores at the risk and cost of the supplier.
- v. The Inspector shall have full and free access at any time during the execution of the contract to the supplier's work for satisfying himself that the goods are being manufactured in accordance with the specification mentioned in the Contract, and he may require the Supplier to make arrangements of inspection of the goods or any part thereof or any material at his premises or at any other place specified by the Inspector and if the Supplier has been permitted to employ the services of a sub-inspection of the goods after they have been inspected by the Inspector for the purpose aforesaid. The decision of the purchaser/ inspection authority in this regard shall be final and binding on the Supplier. All terms and condition of the contract as they apply to the inspection shall also apply to the re- inspection.
- vi. The Supplier shall provide, without any extra charge, all material, tools, labour and assistance of every kind, which the Inspector may demand of him for any test, and examination, which he shall require to be made on the Supplier's premises and the Supplier shall bear and pay all costs attendant thereon. If the Supplier fails to comply with condition aforesaid, the Inspector shall, in his sole judgment, be entitled to remove for test and examination all or any of the goods manufactured by the Supplier to any premises other than his (Supplier's) and in all such cases the Supplier's shall bear the cost of transport/and carrying out such tests elsewhere. A certificate in writing of the Inspector, that the Supplier has failed to provide the facilities and the means for test and examination, shall be final.

- vii. The Supplier shall also provide and deliver for test, free of charge, at such place other than his premises as the Inspector may specify such material or goods as he may require for tests for which Supplier does not have the facilities or special/independent tests.
- viii. The Inspector shall have the right to put all the goods or materials forming part of the same or any part thereof to such tests as he may think fit and proper. The Supplier shall not be entitled to object on any ground whatsoever to the method of testing adopted by the Inspector.
- ix. Goods accepted by the purchase/AIIMS, Raipur and/or its inspector at initial inspection and in final inspection in terms of the contract should in no way dilute purchasers/AIIMS, Raipur's right to reject the same later.
- x. The Purchaser's Inspector reserves the right to may draw samples through random sampling method after receiving the finished goods at destination. All the supplies shall be accompanied with the Manufacturer's certificate that the material conforms to the specifications.

Further to above if on the goods being rejected by the Inspector or AIIMS, Raipur at the destination, the Supplier fails to make satisfactory supply within the stipulated period of delivery the Purchaser shall be at liberty to:-

- a. Require the Suppler to replace the rejected goods forthwith but in any event not later than a period of 30 days from the date of rejection and the Supplier shall bear all cost of such replacement, including freight, if any, on such replacing and replaced goods but without being entitled to any extra payment on that or any other account.
- b. Purchase or authorize the purchase of quantity of the goods rejected or goods of a similar description when goods exactly complying with particulars are not in the opinion of the Purchase, which shall be final, readily available without notice to the supplier at his risk and cost and without affecting the Supplier's liability as regards the supply of any further installment due under the contract, or
- c. Cancel the contract and purchase or authorized the purchase of the goods or goods of a similar description (when goods complying with particulars are not in the opening of the Purchase, which shall be final, readily available) at the risk and cost of the Supplier.
- d. The Inspector shall have the power:-
 - Before any goods or part thereof are submitted for inspection to certify that they cannot be in accordance with the contract owing to the adoption of any unsatisfactory method of manufacture.
 - To reject any goods submitted as not being accordance with particulars.

- To reject the whole of the installment tendered for inspection, if after inspection of such portion thereof as he may in his discretion thinks fit, he is satisfied that the same is unsatisfactory.
- To demand all cost incurred in the inspection and/or test. Cost of test shall be assessed at the rate charged by the Laboratory to private persons for similar work however if goods are accepted all cost incurred shall be born by the Purchaser.

Inspector's decision as regards the rejection shall be final and binding on the Supplier.

10. Guarantee / Warranty, Service, Maintenance:

Warranty

The tenderers must quote for 5 years onsite warranty from the date of completion of the satisfactory installation as certified by the stipulated committee. The Warranty charges **shall not** be quoted separately otherwise the offer shall be summarily rejected. Also the Bidders should submit their quote for subsequent 5 years on site CMC (include free labour, repair, other services & spare parts). Failure to comply this condition will entail the rejection of the Bids. The price comparison shall be made taking into account on basic price and post warranty CMC. The Rate Contracting Authority reserves the right to award CMC. The price of CMC should be quoted according to the cost of equipment. The amount of CMC would be released to the supplier on successful completion of the maintenance of that particular year duly certified by the user department.

Service

The supplier will ensure regular maintenance service by the appropriate engineer having the technical know-how of the equipment. The supplier shall also ensure the presence of resident engineer in the geographical location of this city of Raipur so that he attends the call without loss of time.

Maintenance

It will be mandatory for the supplier to enter into a maintenance contract as applicable below:

a. If the cost of the unit/instrument/equipment is less than INR Five Lakhs, then the supplier has to sign an annual maintenance contract with the purchaser. During this period the supplier shall ensure quality maintenance / check service of minimum 4 times a year in addition to the calls that might be raised by the user department. This contract will be 1 % per annum of the base price (exclusive of taxes / duties) quoted in the financial bid and shall be paid to the supplier at the end of the year with the clearance / satisfaction certificate issued by the user department.

- b. If the cost of the unit/instrument/equipment is more than INR Five Lakhs, then the supplier has to sign a comprehensive maintenance contract with the purchaser. During this period the supplier shall ensure quality maintenance / check service of minimum 4 times a year in addition to the calls that might be raised by the user department. This contract will be 3 % per annum of the base price (exclusive of taxes / duties) quoted in the financial bid and shall be paid to the supplier at the end of the year with the clearance / satisfaction certificate issued by the user department.
 - Non-compliance of any of these conditions or any of the conditions mentioned in the document renders the purchaser to blacklist the supplier along with appropriate legal actions.

11. Downtime penalty Clause

- During the Guarantee/warranty period, desired uptime of 95% of 365 days (24 hrs) if downtime more than 5% the institute shall be entitled to impose penalty equal to amount of 0.05% of the total cost of the equipment per day for the first seven days will be payable by the vendor which will doubled on subsequent weeks along with extension of warranty period by the excess down time period. The vendor must undertake to supply all spares for optimal upkeep of the equipment for at least FIVE YEARS after handing over the unit to the Institute.
- In no case instrument should remain in non-working condition for more than 2 days, beyond which a penalty of 2% of machine cost will be charged per day.

12. Liquidated Damages

If the supplier fails to deliver any or all of the goods or fails to perform the service within the time frame(s) incorporated in the tender, the Purchaser shall, without prejudice to other right and remedies available to the Purchaser under the tender, deduct from the quoted price, as liquidated damages, a sum equivalent to 0.5% per week of delay or part thereof on delayed supply of the quoted price. Once maximum 10% of value of delayed supply is reached, Purchaser may consider termination of the tender.

13. <u>Authorization</u>

It must be mentioned clearly whether tenderer is a manufacturer/sole distributor/sole agent for the items for which he is quoting.

- a. Manufacturer must add a certificate that item(s) is manufactured by them as per range of products
- b. Sole Manufacturers must add a certificate that they are the sole manufacturer of the Item for which they are quoting in this tender enquiry & item is /are their proprietary Item in India. The rate certificate is also required from the sole manufactures that the Rates quoted are the same as they quote to other State/Centre Govt./reputed Private Organization and DGS&D rate for the similar item(s) and these are not higher than those

quoted by them.

Authorized agents must add authority letter from their c. Manufacturer/Principals on the letter head of the manufacturer/principals in Performa given in attach duly supported by a notarized affidavit on Indian Non Judicial Stamp Paper of Rs.10/- (Rupees ten only) that they are quoting Rates on behalf of them. The authorization letter must give/mention the purpose for which it is allowed. The validity period of the authorization letter must be mentioned in the authority letter otherwise tender will be liable to rejection.

14. FORCE MAJEURE:

If, at any time during the subsistence of this contract, the performance in whole or in part by either party of any obligation under this contract is prevented or delayed by reasons of any war or hostility, act of public enemy, civil commotion, sabotage, fire, floods, explosion, epidemics, quarantine restriction, strikers lockout or act of God (hereinafter referred to as events) provided notice of happening of any such eventuality is given by party to other within 21 days from the date of occurrence thereof, neither party hall by reason of such event be entitled to terminate this contract nor shall either party have any claim for damages against other in respect of such non-performance or delay in performance, and deliveries have been so resumed or not shall be final and conclusive.

Further, that if the performance in whole or in part of any obligation under this contract is prevented or delayed by reason of any such event for a period exceeding 60 days, AIIMS, Raipur party may, at least option to terminate the contract.

15. Insolvency etc.:

In the event of the firm being adjudged insolvent or having a receiver appointed for it by a court or any other order under the Insolvency Act made against them or in the case of a company the passing any resolution or making of any order for winding up, whether voluntary or otherwise, or in the event of the firm failing to comply with any of the conditions herein specified AIIMS, Raipur shall have the power to terminate the contract without any prior notice.

16. Breach of Terms and Conditions:

In case of breach of any terms and conditions as mentioned above, the Competent Authority, will have the right to cancel the work order/ job without assigning any reason thereof and nothing will be payable by AIIMS, Raipur. In that event the security deposit shall also stand forfeited.

17. <u>Subletting of Work:</u>

The firm shall not assign or sublet the work/job or any part of it to any other person or party without having first obtained permission in writing of AIIMS, Raipur, which will be

<u>Sign of Bidder</u>

at liberty to refuse if thinks fit. The tender is not transferable. One tenderer shall submit only one tender.

18. <u>Right to call upon information regarding status of work:</u>

The AIIMS, Raipur will have the right to call upon information regarding status of work/ job at any point of time.

19. <u>Terms of payment:</u>

- 1. 70% of the purchase order value will be released after the successful supply & remaining 30% of the amount shall be released after the successful completion of the installment and commissioning of equipment & accessories and demonstration of the performance to the satisfaction of the concerned department.
- 2. No payment shall be made for rejected Stores. Rejected items must be removed by the supplier within two weeks of the date of rejection at their own cost & replace immediately. In case these are not removed these will be auctioned at the risk and responsibility of the suppliers without notice.

20. Arbitration

If any difference arises concerning this agreement, its interpretation on payment to the made thereunder, the same shall be settled out by mutual consultation and negotiation. If attempts for conciliation do not yield any result within a period of 30 days, either of the parties may make a request to the other party for submission of the dispute for decision by an Arbitral Tribunal containing Sole Arbitrator to be appointed by the Secretary, Department of Legal Affairs. Such requests shall be accompanied with a panel of names of three persons to act as the sole arbitrator. In case of such arbitrator refusing, unwilling or becoming incapable to act or his mandate having been terminated under law, another arbitrator shall be appointed in the same manner from among the panel of three persons to be submitted by the claimant. The provision of Arbitration and Conciliation Act, 1990 and the rule framed there under and in force shall be applicable to such proceedings.

21. Legal Jurisdiction:

The agreement shall be deemed to have been concluded in Raipur, Chhattisgarh and all obligations hereunder shall be deemed to be located at Raipur, Chhattisgarh and Court within Raipur, Chhattisgarh will have Jurisdiction to the exclusion of other courts.

Administrative Officer AIIMS, Raipur

Chapter III - Specifications and allied Technical Details

Parameters and Technical Specifications for Executing the Work:

- 1. The participant manufacture/companies having own manufacturing units or their authorized dealer can only participate. Proof of manufacturing is to be attached. Client may also visit and inspect the manufacture set up as deemed fit.
- 2. Manufacturer should be USFDA, European CE and ISO 9001 Certified. Dealers participating should enclose certificate from their parent manufacturer company.
- 3. The firm should be registered and should have the turnover of atleast 50% of the contract amount in the last three financial years.
- 4. The firm has to submit a proof of turnover as mentioned above supported by attested by C.A. documentary materials.
- 5. Tenderer must provide evidence of having supplied to at least 5 reputed government / reputed private organizations in India including at least one government institution.
- 6. The demonstration of the equipment forms an essential part of the tender. The bidder has to arrange for the demonstration of the equipment with no financial assistance from AIIMS Raipur.
- 7. The tenderer can quote for either/all of the schedules mentioned in the bid. If the tenderer is quoting all the Schedules it has to include separate financial bid for each schedule in a separate envelope labeled with the respective schedule on the envelope. Price of the individual instrument/equipment in each schedule should be mentioned in the financial Bid of the quoted schedule, if not the bid for that schedule will be out rightly rejected.
- 8. AIIMS, Raipur also reserves the rights to accept all the equipment/instruments in the given tender or only part of it in any given schedule without assigning any reason.
- 9. The delivery of the items will have to be made at AIIMS, Raipur. No transportation and cartridge charges will be provided for the same.
- 10. The rate quoted should be firm and final and written in ink or typed against each item and should in no case be overwritten.
- ${\rm I}\,/\,{\rm We}$ hereby accept the terms and Conditions given in the tender

(Signature & Stamp of the bidder)

Note- Please sign each page of document including terms & conditions & tender

Chapter - IV Contract Form

TENDER FORM - 1 - TECHNICAL INFORMATION AND UNDERTAKING

(Tenderer may use separate sheet wherever required) (In separate sealed Cover-I super scribed as "Technical Bid")

S. N.	Description	Document Required	Document Supplied (Yes/No)	If yes, provide Reference page number in techno- commercial bid
1.	Name & Address of the manufacture and their authorised dealers/ distributors/ Agency with phone number, email, name and telephone/mobile			
2.	Specify your firm/company is a manufactures/ authorised dealer/distributor / Agency			
3.	Name, Address & designation of the authorized person (Sole proprietor/partner /Director)	Relevant document		
A 4. 5.	Original Equipment Manufacturer's (OEM) Prequalification: (a) Please provide the name, address, and the other details of the OEM. If the OEM is originally incorporated in other country, please furnish such details for India also. (b) Please provide full details of factory /manufacturing units for each item for which the bid is invited. OEM must be a USFDA, European CE & ISO 9001Certified company consistently OEM must be present in India for at least 5 Years with business history	Copy of Valid certificates Company Incorporation certificate		
6.	OEM must have 5+ years of experience supplying and servicing products	Complete installation reports which are older than 2 years		
B 7.	About the tender Offer Tenderer must provide evidence of having supplied government hospital / reputed private hospital organizations in India similar nature of items of atleast 1/3 value of contract amount in the last three years.	 Copy of the all the Supply orders. Satisfaction certificates (along with contact details) from atleast two institutions. 		
С	Tenderer's prequalification			
8.	The average annual turnover of the bidder in the last three financial years should not be less than 50% of contract value.	• Copies of authenticated balance sheet for the past three financial years		

9. Tenderers, if not OEM, must submit OEM's authorization entificate that the tenderer is letter is authorized for selling, and maintaining the equipment quoted for. OEM's authorization entificate that the tenderer is letter 10. Tenderers should submit letter from OEM mentioning that OEM submit letter from OEM mentioning to agree to provide all post-sale installation and maintenance support Undertaking from OEM 12. A partner of the firm, if it is a partnership firm in which case he must have authority to execute the contracts on behalf of the partnership due sconcerning the business of the partnership either by virtue of the partnership agreement or by a power of attorney duly executed by the partners of the firm. Undertaking authorization letter 13. Details of the Earnest Money Deposit (EMD) FDR/DD/BG No: Date: Bank: Payable at Payable at 14. Details of the cost of the Tender documents worth ₹ 5,000/- FDR/DD/BG No: Date: Bank: Payable at Payable at 14. Details of the cost of the Tender documents worth ₹ 5,000/-(Rupees Five Thousand Only) Date: Bank: Payable at FDR/DD/BG No: Date: Bank: Payable at 14. Details of the cost of the Tender documents worth ₹ 5,000/-(Rupees Five Thousand Only) Date: Bank: Payable at FDR/DP/Payable at 15. Whether each page of NIT and its annexure have been signed and stamped Educe of the equipment/instruments quoted with detailed data	S. N.	Description	Document Required	Document Supplied (Yes/No)	If yes, provide Reference page number in techno- commercial bid
10. Tenderers should submit letter from OEM mentioning that OEM shall be fully accountable for the performance of all components of the instruments tendered Undertaking from OEM 11. Tenderers must submit letter from OEM mentioning to agree to provide all post-sale installation and maintenance support Undertaking from OEM 12. A partner of the firm, if it is a partnership firm in which case he must have authority to execute the contracts on behalf of the firm and to refer to arbitration disputes concerning the business of the partnership either by virtue of the partnership agreement or by a power of attorney duly executed by the partners of the firm. Undertaking authorization 13. Details of the Earnest Money Deposit (EMD) FDR/DD/BG No: Date: Bank: Payable at 14. Schedule B - ₹ 60,000/- Date: Bank: Payable at 14. Details of the cost of the Tender documents worth and: Payable at DD/Payable at 14. Details of the cost of the Tender documents worth and: Payable at DD/Payable at 14. Details of the cost of the Tender documents worth and: Payable at: DD/Payable at: 15. Whether each page of NIT and its annexure have been signed and stamped fbt Whether original catalogue of the	9.	authorized for selling, and maintaining the	OEM's authorization letter		
to agree to provide all post-sale installation and maintenance support Undertaking authorization 12. A partner of the firm, if it is a partnership firm in which case he must have authority to execute the contracts on behalf of the firm and to refer to arbitration disputes concerning the business of the partnership either by virtue of the partnership agreement or by a power of attorney duly executed by the partners of the firm. Undertaking authorization D Tender Related Image: Control (Control (C	10.	mentioning that OEM shall be fully accountable for the performance of all components of the	Undertaking from OEM		
which case he must have authority to execute the contracts on behalf of the firm and to refer to arbitration disputes concerning the business of the partnership either by virtue of the partnership agreement or by a power of attorney duly executed by the partners of the firm. letter D Tender Related	11.	to agree to provide all post-sale installation and maintenance support	Undertaking from OEM		
13. Details of the Earnest Money Deposit (EMD) FDR/DD/BG No: Date: Bank: Payable at A. Schedule A - ₹ 4,20,000/- Bank: Payable at B. Schedule B - ₹ 60,000/- Date: Bank: Payable at C. Schedule C - ₹ 1,20,000/- FDR/DD/BG No: Date: Bank: Payable at Date: Bank: Payable at 14. Details of the cost of the Tender documents worth ₹ 5,000/-(Rupees Five Thousand Only) DD/Pay Order No: Date: Bank: Payable at Date: Bank: Payable at 15. Whether each page of NIT and its annexure have been signed and stamped Full 16. Whether original catalogue of the Full	12.	which case he must have authority to execute the contracts on behalf of the firm and to refer to arbitration disputes concerning the business of the partnership either by virtue of the partnership agreement or by a power of attorney duly executed	e		
A. Schedule A - ₹ 4,20,000/- FDR/DD/BG No: Date: Bank: Payable at B. Schedule B - ₹ 60,000/- FDR/DD/BG No: Date: Bank: Payable at C. Schedule C - ₹ 1,20,000/- FDR/DD/BG No: Date: Bank: Payable at 14. Details of the cost of the Tender documents worth ₹ 5,000/-(Rupees Five Thousand Only) DD/Pay Order No: Date: Bank: Payable at 15. Whether each page of NIT and its annexure have been signed and stamped DI/Pay Order No: Date: Bank: Payable at					
A. Schedule A - ₹ 4,20,000/- Date: Bank: Payable at B. Schedule B - ₹ 60,000/- FDR/DD/BG No: Date: Bank: Payable at C. Schedule C - ₹ 1,20,000/- FDR/DD/BG No: Date: Bank: Payable at 14. Details of the cost of the Tender documents worth ₹ 5,000/-(Rupees Five Thousand Only) DD/Pay Order No: Date: Bank: Payable at 15. Whether each page of NIT and its annexure have been signed and stamped Mathematical Stampes 16. Whether original catalogue of the Image: Stampes	13.	Details of the Earnest Money Deposit (EMD)			
B. Schedule B - ₹ 60,000/- Date: Bank: Payable at C. Schedule C - ₹ 1,20,000/- FDR/DD/BG No: Date: Bank: Payable at 14. Details of the cost of the Tender documents worth ₹ 5,000/-(Rupees Five Thousand Only) DD/Pay Order No: Date: Bank: Payable at 15. Whether each page of NIT and its annexure have been signed and stamped Payable at: 16. Whether original catalogue of the Image: Catalogue of the tender		A. Schedule A - ₹ 4,20,000/-	Date: Bank:		
C. Schedule C - ₹ 1,20,000/-Date: Bank: Payable at14.Details of the cost of the Tender documents worth ₹ 5,000/-(Rupees Five Thousand Only)DD/Pay Order No: Date: Bank: Payable at:15.Whether each page of NIT and its annexure have been signed and stamped		B. Schedule B - ₹ 60,000/-	Date: Bank:		
₹ 5,000/-(Rupees Five Thousand Only) Date: Bank: Payable at: 15. Whether each page of NIT and its annexure have been signed and stamped 16. Whether original catalogue of the		C. Schedule C - ₹ 1,20,000/-	Date: Bank:		
been signed and stamped	14.		Date: Bank:		
5 5	15.				
sheet enclosed.		equipment/instruments quoted with detailed data sheet enclosed.			
E Other Relevant Information required		-			
17. Permanent Account Number Copy of the PAN Card 18. Please attach copy of last three years of Income Tax Return Image: Copy of the PAN Card		Please attach copy of last three years of Income	Copy of the PAN Card		

S. N.	Description	Document Required	Document Supplied (Yes/No)	If yes, provide Reference page number in techno- commercial bid
19.	VAT/Service Tax Registration Certificate	Please attach copy		
20.	Acceptance of terms & conditions attached (Yes/No).	Please sign each page of terms and conditions as token of acceptance and submit as part of tender document with technical bid. Otherwise your tender will be rejected.		
21.	Please submit a notarised affidavit on Indian Non judicial stamp paper of Rs. 10/- that no case is pending with the police against the Proprietor/firm/partner or the Company (Agency). Indicate any convictions in the past against the Company/firm/partner. Please also declare that proprietor/firm has never been black listed by any organization.			
22.	Have you previously supplied these items to any government/ reputed private organization? If yes, attach the relevant poof. Please provide a notarised affidavit on Indian Non Judicial stamp paper of Rs. 10/- that you have not quoted the price higher than previously supplied to any government Institute/Organisation/reputed Private Organisation or DGS&D rate in recent past. If you don't fulfil this criteria, your tender will be out rightly rejected.			
23.	Any other information important in the opinion of the tenderer			
24.	Kindly mention the total number of pages in the tender document.			

Note:

- i. Page number/serial number may be given to each and every page of Tender Documents and photocopies of the attested documents attached. Mention Page number, wherever the copy (ies) of the document(s) is kept.
- ii. In case of non-fulfillment of any of the above information/ document(s), the Tender will be summarily rejected without giving any notice.

(Dated Signature of the Tenderer with stamp of firm)

Declaration by the Tenderer:

- That I/we have carefully studied all the terms & conditions of NIT and shall abide by it.
- 2) That I/We shall supply the items of requisite quality.
- 3) That I/We undertake that the information given in this tender are true and correct in all respect and I/We hold the responsibility for the same.

(Signature of Tenderer with seal)

Name:

Address :

"Multipara & Neonatal Multipara Monitor" AIIMS, Raipur <u>FINANCIAL BID for SCHEDULE – A</u>

				-II super scribed	Financial Diu Ior	, , , , ,		
S.	Item Description	Qty of	Unit Price in INR	Custom duty in	Taxes (if	Service Tax (if	Total Unit Price	Total price of (Unit
No.		units		INR (if applicable)	applicable) VAT /	applicable) in INR	(including all taxes)	price x Quantity)
					Sales Tax/etc in			r ··· (································
					INR			
					INR			
1	2	3	4	5	6	7	(4+5+6+7)=8	(3x8)=9
1	MULTIPARA	14						
	MONITOR							
	(HIGH END)							
	Accessories							
-	CMC Total for Five Y	oare (De	taila ia to ho montion o	d in concrete Table)	I	I		
		cars (De		i ili separate Tablej				
	Grand Total*:							1

(In sealed Cover-II super scribed "Financial Bid for Schedule – A")

The Grand Total * will be the deciding factor for L1 provided all the other conditions mentioned in the tender document (GCC, SCC and the technical conditions) are fulfilled.

DATE:

SIGNATURE WITH NAME AND SEAL

"Multipara & Neonatal Multipara Monitor" AIIMS, Raipur <u>FINANCIAL BID for SCHEDULE – B</u>

				-II super scribeu	Fillalicial Diu Iul S	,	r	1
S.	Item Description	Qty of	Unit Price in INR	Custom duty in	Taxes (if	Service Tax (if	Total Unit Price	Total price of (Unit
No.	-	units		INR (if applicable)	applicable) VAT /	applicable) in INR	(including all taxes)	price x Quantity)
					Sales Tax/etc in	TT		r ··· (································
					INR			
1	2	2			1			
1	2	3	4	5	6	1	(4+5+6+7)=8	(3x8)=9
1		0.0						
1	NEONATAL	02						
	MULTIPARA							
	MONITOR							
	(HIGH END)							
	A							
	Accessories							
	CMC Total for Five Y	'ears (De	tails is to be mentioned	d in senarate Table)				
	Grand Total*:							

(In sealed Cover-II super scribed "Financial Bid for Schedule – B")

The Grand Total * will be the deciding factor for L1 provided all the other conditions mentioned in the tender document (GCC, SCC and the technical conditions) are fulfilled.

DATE:

SIGNATURE WITH NAME AND SEAL

"Multipara & Neonatal Multipara Monitor" AIIMS, Raipur <u>FINANCIAL BID for SCHEDULE – C</u>

				-II super scribed	Financial Diu Ior	/		
S.	Item Description	Qty of	Unit Price in INR	Custom duty in	Taxes (if	Service Tax (if	Total Unit Price	Total price of (Unit
No.		units		INR (if applicable)	applicable) VAT /	applicable) in INR	(including all taxes)	price x Quantity)
					Sales Tax/etc in			
					INR			
1	2	3	4	5	6	7	(4+5+6+7)=8	(3x8)= 9
1		00						
1	MULTIPARA MONITOR	08						
	Accessories							
	CMC Total for Five Y	lears (De	tails is to be mentioned	d in separate Table)				
	Grand Total*:							

(In sealed Cover-II super scribed "Financial Bid for Schedule – C")

The Grand Total * will be the deciding factor for L1 provided all the other conditions mentioned in the tender document (GCC, SCC and the technical conditions) are fulfilled.

DATE:

SIGNATURE WITH NAME AND SEAL

PRICE SCHEDULE FOR COMPREHENSIVE MAINTENANCE CONTRACT (C.M.C) AFTER EXPIRY OF WARRANTY

(RATES SHOULD BE QUOTED IN INDIAN RUPEES ONLY)

Sr	SME	Name of	For Sixth	For	For Eighth	For Ninth	For Tenth
No	Code	the	year with	Seventh	year with	year with	year with
	No.	Equipment	spare parts	year with	spare parts	spare parts	spare parts
			& labour	spare parts	& labour	& labour	& labour
				& labour			
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)

SCHEDULE – A/B/C

Place: Date:

> Signature Name in Capital Letters Designation

SPECIAL CONDITIONS

- 1. The bidders should submit the relevant certificates / evidence of previous supply to other hospitals. If required, the technical committee may enquire from the other hospitals where the bidders have supplied the material.
- 2. The bidders should also submit a certificate from the relevant authority as to the quality of the equipment.
- 3. The bidder should not have been blacklisted before.
- 4. The bidders shall also arrange for the demonstration of their equipment to the concerned committee regarding the quality aspect.

Declaration by the Bidder:

- 1. This is to certify that I/We before signing this tender have read and fully understood all the terms and conditions contained in Tender document regarding terms & condition of the contract, rules regarding purchase of Maxillofacial Surgery Instruments . I/we agree to abide them.
- 2. No other charges would be payable by Client and there would be no increase in rates during the Contract period.

Place:	(Signature	of	Bidder	with	seal)
Date:					

Name : Seal : Address:

Annexure-I

TECHNICAL SPECIFICATION FOR MULTIPARA & NEONATAL MULTIPARA MONITOR

TECHNICAL SPECIFICATIONS

General Specifications:

- 1. All the material /equipment should be European CE/ US FDA/ EN ISO Certified.
- 2. All the Electronic equipments should comply with Electrical safety conforms to standards for electrical safety IEC 60601-1.
- 3. All the equipment's power input should be 220- 240V AC, 50Hz fitted with Indian plug.

Schedule-A

MULTIPARA MONITOR (HIGH END) (14 Nos.)

No.	Name of	Specifications Required for the Equipment to be purchased
	Equipment	
	General:	 Parameters - ECG, heart rate, respiratory rate, SpO2, NiBP, Dual IBP, EtCO2, Dual Temperature Should be Modular and capable of being connected to a central station The equipment should come with all standard accessories required to run all parameters. Waveform display: at least 8 channels at a time, user selectable Digital display: Heart rate, respiratory rate, oxygen saturation, temperature, Blood Pressure (systolic, diastolic, mean) System should be compatible with HIS. System should be US FDA & European CE approved for quality assurance. Monitor must be able to connect to central monitoring station and should use single network for all kind of networking with the central station or other hospital information system (HIS). It should have at least eight beds wired/wirelessly on central station with at least two waveforms from each bedside being viewed. It should have dual display, one for continuous display of all beds and other for trend review, full disclosure etc.
1.	Individual	 Wall-mountable and pivotable
	Monitors :	 Medical grade, TFT Flat screen, slim size, at least 19" display
		 Flexible display mode for various monitoring needs Should be knob control/ touch screen
		 Should be knob control/ touch screen Viewing angle at least 90o
		 Bigger font of numeric should also be available
		 Should have standby mode for temporary leaving of patients.
		 Adjustable contrast and brightness
		Should have facility to record data for individual patients identifiable by their
		name and hospital registration number

ations Required for the Equipment to be purchased
ng modules complete with their accessories for each monitor:
t rate
iration
gen saturation
perature: 2 ports
nvasive Blood pressure
sive blood pressure 2 ports
02
invasive cardiac output
ast 3-lead selectable ECG
in arrhythmia monitoring in all leads
ilt ST segment analysis and arrhythmia detection facility
lay of 2 ECG leads simultaneously at a time
t rate range 20-250 bpm
racy ± 5 bpm
lay sweep speeds 12.5, 25 mm/sec (user adjustable)
aging time: user selectable up to 8 seconds
amplitude user adjustable
orillator protected sured by transthoracic impedance using the same ECG lead
ge 0 to 150 breaths/min
$aracy \pm 2 \text{ bpm}$
lay sweep speeds 6.25, 12.5 & 25 mm/sec (user adjustable)
aging time: user selectable up to 8 seconds
selectable apnea alarm time
mo-SET technology to take care of low perfusion states and
on artifacts
wavelength LED pulse oximetry
ge 1 to100%
2 accuracy : ± 2 % (70-100% range)
aging time: user selectable up to 8 seconds
ysmographic waveform display
em must display perfusion index (PI %) from SpO_2 as an
cation of pulse strength at the sensor site.
nannels
inuous digital display of two site temperatures
ge: 25-50 degree Celsius
lution: ± 0.1 degree Celsius
v: + 0.1 degree Celsius
uld provide skin temperature probe and rectal temperature probe
every monitor

No.	Name of Equipment	Specifications Required for the Equipment to be purchased
	Equipment	
7.	Noninvasive Blood pressure:	 Capable of measuring blood pressure including in neonates weighing 500 g Microprocessor software with unit in mmHg Oscillometric technique Manual, auto and time limited stat modes User selectable automatic time intervals Display systolic, diastolic and mean BP Blood pressure range Systolic : 30-250 mm Hg Diastolic : 10-100 mm Hg Mean: 20 - 100 mmHg Pulse rate range : 20-250 bpm Cuff : auto deflate with over pressure protection
		Should automatically establish zero reference after each reading
8.	Invasive Blood pressure	 At least 2 channels Compatible with reusable and disposable pressure transducers Transducer should allow continuous infusion into the artery through an infusion pump while pressure is simultaneously displayed Input through pressure transducer that functions through a fluid filled catheter system Unit: mmHg Should allow continuous fluid infusion into the artery /vein through an infusion pump without any volume limitation Compatible with arterial BP, CVP and intracranial pressure monitoring catheters with user selectable display names Range 0-350 mmHg Display resolution: ±1 mmHg Accuracy ± 1mmHg Digital waveform display User selectable pressure channel display Should be Compatible with ICP monitoring system Name of manufacturer of compatible ICP monitoring system should be provided with documentary evidence. Monitor must measure dynamic preload parameters such as pulse pressure variation (PPV) and systolic pressure variation (SPV) from arterial waveform and display on main screen.)
9.	EtCO2	 Should provide mainstream modules Warm up time: capnogram displayed in less than 15 sec Measurement method: infrared spectrum Unit: %, mmHg, kPa CO2 Accuracy: +/- 2.0 mmHg Measurement range: 0-150 mmHg Resolution: 1 mmHg Resp rate accuracy +/- 1 rpm Range of resp rate measurement: 0-150/ min

No.	Name of	Specifications Required for the Equipment to be purchased
	Equipment	
10.	User selectable	 High and low heart rate
10.	alarms	 High and low respiratory rate
		 Apnea with adjustable time 5-20 seconds
		 High and low saturation
		 High and low SBP
		 High and low DBP
		 High and low MAP
		 Probe failure
		 Poor signal
		 Power failure
		 Audio & visual alarms with message with separate alarm indicator
		with 360° viewing.
11.	Trends	 Memory storage : at least 96 hours
11.	TICHUS	 Data display interval : not more than 20 sec
		 Display range : last ½ hour to 72 hours
		 Graphical and tabular format of display of variables
12.	Power	220/240 V
14.	FUWEI	50/60 Hz AC
		Rechargeable internal battery with a back up of at least 1 hr
		Safety class category A
13.	Manuals:	One set of operator & service manuals with each monitor
		one set of operator w service manuals with cach monitor
14.	Comprehensive warranty period :	5 years and CMC for 5 years after warranty
15.	wallancy period.	Availability of spares for at least 10 years after date of installation
16.		Comprehensive warranty and CAMC would include all parts-plastic,
10.		metallic, glass, batteries and rubber except the consumable accessories
		listed below against item no. 22. Comprehensive warranty and CAMC would
		include periodic checking and periodic calibration of all parameters strictly
		as per manufacturer's recommendations (at least every 3 month) and any
		spares, gases or standards required for that.
17.		Should have online and telephonic registration of the complaints
		Should have ensident service engineer in Raipur and should be available 24 x
18.		
10		7 to solve the complaints. Down time of the equipment will start from the time of lodgment of first
19.		
		complaint.
20.		complaint. If machine is not made fully functional within 24 hours of the lodgment of
		complaint. If machine is not made fully functional within 24 hours of the lodgment of complaint, a standby machine of similar configuration must be provided.
		complaint. If machine is not made fully functional within 24 hours of the lodgment of complaint, a standby machine of similar configuration must be provided. Failure to do so will invite an increase in the period of comprehensive
		complaint. If machine is not made fully functional within 24 hours of the lodgment of complaint, a standby machine of similar configuration must be provided. Failure to do so will invite an increase in the period of comprehensive warranty or CAMC by 7 times of the downtime period. (i.e. 7 days for every
20.		complaint. If machine is not made fully functional within 24 hours of the lodgment of complaint, a standby machine of similar configuration must be provided. Failure to do so will invite an increase in the period of comprehensive warranty or CAMC by 7 times of the downtime period. (i.e. 7 days for every 1 day of downtime).
		 complaint. If machine is not made fully functional within 24 hours of the lodgment of complaint, a standby machine of similar configuration must be provided. Failure to do so will invite an increase in the period of comprehensive warranty or CAMC by 7 times of the downtime period. (i.e. 7 days for every 1 day of downtime). Should be able to provide training of all healthcare personnel during first 1
20. 21.		 complaint. If machine is not made fully functional within 24 hours of the lodgment of complaint, a standby machine of similar configuration must be provided. Failure to do so will invite an increase in the period of comprehensive warranty or CAMC by 7 times of the downtime period. (i.e. 7 days for every 1 day of downtime). Should be able to provide training of all healthcare personnel during first 1 month of installation in the group of 5 trainees per session.
20.		 complaint. If machine is not made fully functional within 24 hours of the lodgment of complaint, a standby machine of similar configuration must be provided. Failure to do so will invite an increase in the period of comprehensive warranty or CAMC by 7 times of the downtime period. (i.e. 7 days for every 1 day of downtime). Should be able to provide training of all healthcare personnel during first 1 month of installation in the group of 5 trainees per session. Essential Accessories for 1 monitor
20. 21.		 complaint. If machine is not made fully functional within 24 hours of the lodgment of complaint, a standby machine of similar configuration must be provided. Failure to do so will invite an increase in the period of comprehensive warranty or CAMC by 7 times of the downtime period. (i.e. 7 days for every 1 day of downtime). Should be able to provide training of all healthcare personnel during first 1 month of installation in the group of 5 trainees per session. Essential Accessories for 1 monitor The following quantities are to be supplied for every monitor with the initial
20. 21.		 complaint. If machine is not made fully functional within 24 hours of the lodgment of complaint, a standby machine of similar configuration must be provided. Failure to do so will invite an increase in the period of comprehensive warranty or CAMC by 7 times of the downtime period. (i.e. 7 days for every 1 day of downtime). Should be able to provide training of all healthcare personnel during first 1 month of installation in the group of 5 trainees per session. Essential Accessories for 1 monitor The following quantities are to be supplied for every monitor with the initial order:
20. 21.		 complaint. If machine is not made fully functional within 24 hours of the lodgment of complaint, a standby machine of similar configuration must be provided. Failure to do so will invite an increase in the period of comprehensive warranty or CAMC by 7 times of the downtime period. (i.e. 7 days for every 1 day of downtime). Should be able to provide training of all healthcare personnel during first 1 month of installation in the group of 5 trainees per session. Essential Accessories for 1 monitor The following quantities are to be supplied for every monitor with the initial order: ECG/Respiration
20. 21.		 complaint. If machine is not made fully functional within 24 hours of the lodgment of complaint, a standby machine of similar configuration must be provided. Failure to do so will invite an increase in the period of comprehensive warranty or CAMC by 7 times of the downtime period. (i.e. 7 days for every 1 day of downtime). Should be able to provide training of all healthcare personnel during first 1 month of installation in the group of 5 trainees per session. Essential Accessories for 1 monitor The following quantities are to be supplied for every monitor with the initial order:

No.	Name of Equipment	Specifications Required for the Equipment to be purchased
		Oxygen saturation
		 Patient extension cables: 2
		 Reusable neonatal wrap around probes: 4
		 Reusable pediatric clip/ finger probes: 4
		Temperature
		 Reusable surface (skin) temperature probes: 2
		 Reusable rectal temperature probes: 2
		NIBP
		 Patient extension cable – 2
		 Disposable NIBP cuffs suitable for neonates, children and adults
		(<1000g, 1000-2000g, >2000g, pediatric, adolescent and adult): 5 no
		of each size
		IBP
		 Transducer connecting cables: 2
		 Reusable pressure transducer: 5
		 Disposable pressure dome kit with neonatal flush device: 10
		 Quotation must include a compliance statement and in addition,
		each of the above points is marked in the technical brochure. Points
		not covered in the brochure must be specifically addressed in a
		separate certificate.
		Manuals: One set of operator & service manuals with each monitor
		-
		should be able to provide training of an incutificate personnel during
		 first 1 month of installation in the group of 5 trainees per session. EDA (USA) or CE certificate must be enclosed
		TER (Corr) of CE continente must be cherosed.
		onoice physical demonstration of the machine with an standard
		actual accessories of the same make which the firm intends to
		supply will be mandatory if demanded by the technical committee.
		The ventilator with all the accessories has to be left in the unit for
		demonstration on real patients for at least 7 days.
		Prices of the above consumable accessories should be quoted separately,
		which will be fixed for the duration of comprehensive warranty and CAMC
		(i.e., for 10 years)
		Warranty and CAMC:
		• Comprehensive warranty period: 5 years and CMC for 5 years after
		warranty
		• Availability of spares for at least 10 years after date of installation
		• Comprehensive warranty and CAMC would include all parts-plastic,
		metallic, glass, batteries and rubber (without any exclusion) except
		the consumable accessories listed above.
		Comprehensive warranty and CAMC would include periodic checking
		and periodic calibration of all parameters strictly as per
		manufacturer's recommendations (at least every 3 month) and any
		spares or standards required for that.
		Should have online and telephonic registration of the complaints
		• Should have resident service engineer in Raipur and should be
		available 24 x 7 to solve the complaints.
		• Down time of the equipment will start from the time of lodgment of
		first complaint.
		• The company must ensure that the machine remains FULLY

No.	Name of Equipment	Specifications Required for the Equipment to be purchased
		 functional all the time for the period of warranty and CAMC. If machine is not made fully functional within 24 hours of the lodgement of complaint (even for single parameters), a standby machine of similar configuration must be provided. Failure to do so will invite an increase in the period of comprehensive warranty or CAMC by 7 times of the downtime period. (i.e. 7 days for every 1 day of downtime). This will be valid even for holidays. No request in this regard will be entertained on the pretext of on availability of items with the supplier/company. Quoting Price and Rates: Rates should be quoted in full (indicating rates of items quoted, VAT, CST, Octroi, Insurance, Packing, freight excise) and separately. The total cost of accessory items along with the cost of machine will be considered for comparative purpose among companies. If the firm does not list any item in the tender, no payment will be made for the items required for complete operation of the machine. The firm will be obliged to supply any omitted items for the entire duration of warranty free of cost and no representation on this will be entertained. If the company fails to quote for any item, it has to provide the item free of cost for three years.

<u>Schedule-B</u>

NEONATAL MULTIPARA MONITOR -HIGH END(2 Nos.)

No.	Name of Equipment	Specifications Required for the Equipment to be purchased
	Distribution outline:	 Basic parameters (ECG/heart rate, O2 saturation, NIBP, respiration & temperature) – in all monitors Invasive BP module: in all monitors Microstream end tidal CO2 module: in all monitors EEG module: in all monitor
	General:	 Upgradable Modular system, capable of being connected to a central station The equipment should come with all standard accessories required to run all parameters.
	Waveform display:	at least 6 channels, user selectable
	Digital display:	 Heart rate, respiratory rate, oxygen saturation, temperature, Blood Pressure (systolic, diastolic, mean), EtCO2(wherever applicable) Should be upgradable for measurement of cardiac output/SvO2 Should be possible to move the Microstream end tidal CO2 and EEG modules from one monitor to another. Should be able to remotely access the patient monitoring system via internet System should be compatible with HIS and be HL-7 compliant Ready to run web based applications like HIS, PACS, RIS, LIS etc on patient monitor screen itself without need of additional server/PC hardware and software as standard supply.

No.	Name of	Specifications Required for the Equipment to be purchased
	Equipment	
		Individual Monitors :
		Wall mountable and pivotable
		• Medical grade, TFT Flat screen, slim size, at least 19" display
		Screen resolution at least 1280x1024 pixels
		 Clear bright color display with large character size Should have both remote/ mouse control and knob control/ touch
		screen
		• Viewing angle at least 900
		Adjustable contrast and brightness
		Ability to zoom any parameters
		Ability to adjust individual alarms
		Ability to change color of the trace by user DO 0200 interface for data accuracy instance
		 RS 232C interface for data communication UPS system with at least 1 hour backup time
		 Should provide a high quality thermal recorder interchangeable module, 1
		no with each monitor.
		• Store and review trends for at least 72 hours
		1. Parameters monitored :
		• The following modules complete with their accessories:
		Heart rate/ECG
		Respiration
		Oxygen saturation
		• Temperature
		Noninvasive Blood pressure
		Invasive blood pressure
		• EEG (2 monitors), 'micro stream' EtCO2 (2 monitors)
		2. Heart rate/ECG:
		• At least 3-lead selectable ECG
		Built in arrhythmia monitoring in all leads
		Inbuilt ST segment analysis and arrhythmia detection facility
		• Display of 2 ECG leads simultaneously at a time
		Heart rate range 20-240 bpm
		• Accuracy + 5 bpm
		• Display sweep speeds 12.5, 25 mm/sec (user adjustable)
		• Averaging time: user selectable up to 8 seconds
		• ECG amplitude user adjustable
		Defibrillator protected
		3. Respiratory rate
		Measured by transthoracic impedance using the same ECG lead
		Range 0 to 150 breaths/min
		• Accuracy + 2 bpm
		• Display sweep speeds 6.25, 12.5 & 25 mm/sec (user adjustable)
		Averaging time: user selectable up to 8 seconds
		User selectable apnea alarm time
		4. Oxygen Saturation
		• Masimo-SET technology to take care of low perfusion states and motion
		artefacts.
		Dual wavelength LED pulse oximetry
		• Range 1 to100%

 SpO2 accuracy : + 2 % (70-100% range) Averaging time: user selectable up to 8 seconds Plethysmographic waveform display Temperature Skin type capable of recording both central and temperature Continuous digital display of two site temperatures Range: 25-50 degree Celsius Recolution: ± 0.1 degree Celsius Accuracy: + 0.1 degree Celsius Accuracy: + 0.1 degree Celsius Capable of measuring blood pressure in neonates weigh g Microprocessor software with unit in mmHg Oscillometric technique Manual, auto and time limited stat modes User selectable automatic time intervals Display systolic, diastolic and mean BP Blood pressure range Systolic BP : 30-150 mm Hg Diastolic BP : 10-100 mm Hg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each Hoastive Blood pressure A teast 2 channels Compatible with reusable and disposable pressure trans Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation 	rchased
 Averaging time: user selectable up to 8 seconds Plethysmographic waveform display 5. Temperature Skin type capable of recording both central and temperature Continuous digital display of two site temperatures Range: 25-50 degree Celsius Resolution: ± 0.1 degree Celsius Accuracy: ± 0.1 degree Celsius 6. Non-invasive Blood pressure : Capable of measuring blood pressure in neonates weigh g Microprocessor software with unit in mmHg Oscillometric technique Manual, auto and time limited stat modes User selectable automatic time intervals Display systolic, diastolic and mean BP Blood pressure range Systolic BP : 30-150 mm Hg Diastolic BP : 10-100 mm Hg Mean: BP 20 - 100 mmHg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure transs Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arte 	
 Plethysmographic waveform display 5. Temperature Skin type capable of recording both central and temperature Continuous digital display of two site temperatures Range: 25-50 degree Celsius Resolution: ± 0.1 degree Celsius Accuracy: + 0.1 degree Celsius 6. Non-invasive Blood pressure : Capable of measuring blood pressure in neonates weigh g Microprocessor software with unit in mmHg Oscillometric technique Manual, auto and time limited stat modes User selectable automatic time intervals Display systolic, diastolic and mean BP Blood pressure range Systolic BP : 30-150 mm Hg Diastolic BP : 10-100 mm Hg Mean: BP 20 - 100 mmHg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure trans Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arte 	
 5. Temperature Skin type capable of recording both central and temperature Continuous digital display of two site temperatures Range: 25-50 degree Celsius Resolution: ± 0.1 degree Celsius Accuracy: + 0.1 degree Celsius 6. Non-invasive Blood pressure : Capable of measuring blood pressure in neonates weigh g Microprocessor software with unit in mmHg Oscillometric technique Manual, auto and time limited stat modes User selectable automatic time intervals Display systolic, diastolic and mean BP Blood pressure range Systolic BP : 30-150 mm Hg Diastolic BP : 10-100 mm Hg Mean: BP 20 - 100 mmHg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure transs Transducer should allow continuous infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arte 	
 Skin type capable of recording both central and temperature Continuous digital display of two site temperatures Range: 25-50 degree Celsius Resolution: ± 0.1 degree Celsius Accuracy: + 0.1 degree Celsius 6. Non-invasive Blood pressure : Capable of measuring blood pressure in neonates weigh g Microprocessor software with unit in mmHg Oscillometric technique Manual, auto and time limited stat modes User selectable automatic time intervals Display systolic, diastolic and mean BP Blood pressure range Systolic BP : 30-150 mm Hg Diastolic BP : 10-100 mm Hg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure transs Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arte 	
 Continuous digital display of two site temperatures Range: 25-50 degree Celsius Resolution: ± 0.1 degree Celsius Accuracy: + 0.1 degree Celsius 6. Non-invasive Blood pressure : Capable of measuring blood pressure in neonates weigh g Microprocessor software with unit in mmHg Oscillometric technique Manual, auto and time limited stat modes User selectable automatic time intervals Display systolic, diastolic and mean BP Blood pressure range Systolic BP : 30-150 mm Hg Diastolic BP : 30-150 mm Hg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure transs Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arte 	peripheral skin
 Resolution: ± 0.1 degree Celsius Accuracy: + 0.1 degree Celsius 6. Non-invasive Blood pressure : Capable of measuring blood pressure in neonates weigh g Microprocessor software with unit in mmHg Oscillometric technique Manual, auto and time limited stat modes User selectable automatic time intervals Display systolic, diastolic and mean BP Blood pressure range Systolic BP : 30-150 mm Hg Diastolic BP : 10-100 mm Hg Mean: BP 20 - 100 mmHg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure transs Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arte 	
 Resolution: ± 0.1 degree Celsius Accuracy: + 0.1 degree Celsius 6. Non-invasive Blood pressure : Capable of measuring blood pressure in neonates weigh g Microprocessor software with unit in mmHg Oscillometric technique Manual, auto and time limited stat modes User selectable automatic time intervals Display systolic, diastolic and mean BP Blood pressure range Systolic BP : 30-150 mm Hg Diastolic BP : 10-100 mm Hg Mean: BP 20 - 100 mmHg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure transs Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arte 	
 Accuracy: + 0.1 degree Celsius 6. Non-invasive Blood pressure : Capable of measuring blood pressure in neonates weigh g Microprocessor software with unit in mmHg Oscillometric technique Manual, auto and time limited stat modes User selectable automatic time intervals Display systolic, diastolic and mean BP Blood pressure range Systolic BP : 10-100 mm Hg Mean: BP 20 - 100 mmHg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure transs Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arte 	
 6. Non-invasive Blood pressure : Capable of measuring blood pressure in neonates weigh g Microprocessor software with unit in mmHg Oscillometric technique Manual, auto and time limited stat modes User selectable automatic time intervals Display systolic, diastolic and mean BP Blood pressure range Systolic BP : 30-150 mm Hg Diastolic BP : 10-100 mm Hg Mean: BP 20 - 100 mmHg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure transs Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arte 	
 Capable of measuring blood pressure in neonates weigh g Microprocessor software with unit in mmHg Oscillometric technique Manual, auto and time limited stat modes User selectable automatic time intervals Display systolic, diastolic and mean BP Blood pressure range Systolic BP : 30-150 mm Hg Diastolic BP : 10-100 mm Hg Mean: BP 20 - 100 mmHg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure trans Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arte 	
 Microprocessor software with unit in mmHg Oscillometric technique Manual, auto and time limited stat modes User selectable automatic time intervals Display systolic, diastolic and mean BP Blood pressure range Systolic BP : 30-150 mm Hg Diastolic BP : 10-100 mm Hg Mean: BP 20 - 100 mmHg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure transs Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arte 	ing 400 g to 5000
 Oscillometric technique Manual, auto and time limited stat modes User selectable automatic time intervals Display systolic, diastolic and mean BP Blood pressure range Systolic BP : 30-150 mm Hg Diastolic BP : 10-100 mm Hg Mean: BP 20 - 100 mmHg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure transs Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arte 	
 Manual, auto and time limited stat modes User selectable automatic time intervals Display systolic, diastolic and mean BP Blood pressure range Systolic BP : 30-150 mm Hg Diastolic BP : 10-100 mm Hg Mean: BP 20 - 100 mmHg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure transs Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arte 	
 User selectable automatic time intervals Display systolic, diastolic and mean BP Blood pressure range Systolic BP : 30-150 mm Hg Diastolic BP : 10-100 mm Hg Mean: BP 20 - 100 mmHg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure transs Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arter 	
 Display systolic, diastolic and mean BP Blood pressure range Systolic BP : 30-150 mm Hg Diastolic BP : 10-100 mm Hg Mean: BP 20 - 100 mmHg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure transs Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arter 	
 Blood pressure range Systolic BP : 30-150 mm Hg Diastolic BP : 10-100 mm Hg Mean: BP 20 - 100 mmHg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure trans Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arterial P, CVP, pulmonary arterial 	
 Systolic BP : 30-150 mm Hg Diastolic BP : 10-100 mm Hg Mean: BP 20 - 100 mmHg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure trans Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arter 	
 Systolic BP : 30-150 mm Hg Diastolic BP : 10-100 mm Hg Mean: BP 20 - 100 mmHg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure trans Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arter 	
 Mean: BP 20 - 100 mmHg Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure trans Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arteriant 	
 Pulse rate range : 20-240 bpm Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure trans Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arterial 	
 Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure trans Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arterial 	
 Cuff : auto deflate with over pressure protection Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure trans Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arterial 	
 Should automatically establish zero reference after each 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure trans Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arterial 	
 7. Invasive Blood pressure At least 2 channels Compatible with reusable and disposable pressure trans Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arterial 	reading
 At least 2 channels Compatible with reusable and disposable pressure trans Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arterial 	5
 Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arterial 	
 Transducer should allow continuous infusion into the infusion pump while pressure is simultaneously display pressure transducer that functions through a fluid filled Unit: mmHg Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arterial 	ducers
 Should allow continuous fluid infusion into the artery infusion pump without any volume limitation Compatible with arterial BP, CVP, pulmonary arterial 	artery through an red Input through
pump without any volume limitationCompatible with arterial BP, CVP, pulmonary arte	/vein through an
Compatible with arterial BP, CVP, pulmonary arte	
	ry pressure and
pressure monitoring catheters	
 Range 0-300 mmHg 	
 Display resolution: ±1 mmHg 	
 Accuracy ± 1mmHg 	
 Digital waveform display 	
User selectable pressure channel display	
8. EEG	
• EEG module should be interchangeable with any of the	nonitors
Input: 6 lead	101111015
 Sensitivity: 20, 50,100,250/µV/cm 	

No.	Name of	Specifications Required for the Equipment to be purchased
	Equipment	
		Display: Left or right sided waveform
		• Small, cup type EEG electrodes and lead set kit suitable for neonatal use
		with a low impedance
		9. Microstream end tidal capnography (EtCO2)
		Module should be interchangeable with any of the monitors
		Microstream technology with neonatal mode
		Display of both waveform and numerical values
		• Should be usable in intubated as well as non-intubated neonates
		• Measured parameters: EtCO2, CO2 waveform, Respiratory rate
		• CO2 range – 0-150 mmHg
		• Respiratory rate – 0-150 breaths / min
		• Display – in mmHg and %
		Accuracy - ±2 mmHg (0-38 mmHg)
		10. User selectable alarms
		High and low heart rate
		High and low respiratory rate
		 Apnea with adjustable time 5-20 seconds Uigh and law acturation
		High and low saturation
		High and low SBP
		High and low DBPHigh and low MAP
		 High and low MAP High and low EtCO2
		 Probe failure
		 Poor signal
		 Power failure
		 Audio & visual alarms with message
		11. Trends
		Memory storage : at least 24 hours
		 Data display interval : not more than 20 sec
		 Display range : last ½ hour to 24 hours
		 Graphical and tabular format of display of variables
		12. Power
		• 220/240 V
		• 50/60 Hz AC
		 Rechargeable internal battery with a back up of at least 1 hr
		13. Communications with Information Management Systems:
		a. To provide HL-7 compatible server for sending and receiving information to
		and from the monitoring network to and from Hospital Information
		System, Laboratory information etc for integration of various information
		b. To provide suitable facility for sending and receiving DICOM Compatible
		Radiological Images like Ultrasound, X-Ray etc to and from the monitoring
		network to and from Hospital Information System, Radiology Information
		System etc for integration of various information
		14. Manuals : Operator & service manuals
		15. Should be approved & certified by FDA (USA) and European CE
		(certificate to be submitted)
		16. Manufacturer should have ISO certification for quality standards
		17. Shall meet the safety requirements as per IEC 60601-2-27:1994-

No.	Name of	Specifications Required for the Equipment to be purchased
	Equipment	
		Medical electrical equipment—Part 2: Particular requirements for the safety
		of electrocardiographic monitoring equipment
		18. Availability of spares for at least 10 years after date of installation
		19. Warranty and CMC would include the periodic calibration of all parameters
		strictly as per manufacturer's recommendations and any spares or
		standards required for that.
		20. Onsite physical demonstration of the monitor with all the requested
		modules will be mandatory 21. Should have local service facility and should have the necessary
		equipments to carry out preventive maintenance test
		22. Essential Accessories
		 The following quantities are to be supplied with the initial order:
		 ECG/Respiration per monitor.
		 ECG/Respiration per monitor. ECG patient cable : 2
		 ECG lead wires set (at least 3 leads) : 2 sets Disposable small ECG electrodes for preterm neonates: 50 sets (set of 3)
		 Disposable small Led electrodes for preterm neonates. 50 sets (set of 5) Oxygen saturation
		 Patient extension cables: 2
		Reusable neonatal wrap around probes: 2
		Reusable ear probe – 2 Temperature
		Temperature Bauachla aurface (alrin) temperature probase 2
		 Reusable surface (skin) temperature probes: 2 NIBP
		 NIBP Patient extension cable – 2
		Disposable NIBP cuffs of sizes suitable for neonates (<1000g, 1000-2000g, and
		 >2000g): 10 no of each size (total 30 no)
		IBP
		• Transducer connecting cables: 2
		Reusable pressure transducer: 4
		• Disposable pressure dome kit with neonatal flush device: 50
		Microstream capnography (EtCO2)
		Disposable EtCO2 sensors: Through ET tube: 50
		EEG
		• Patient cable: 2
		• Small, cup type EEG electrodes suitable for neonates with lead set kit: 2
		23. Prices of above consumables should be quoted separately and frozen for the
		period including warranty and CMC period.
		24. Shall meet IEC-60601-1-2 :2001(Or Equivalent BIS) General Requirements
		of Safety for Electromagnetic Compatibility. Or should comply with
		89/366/EEC; EMC-directive
		25. The unit shall be capable of being stored continuously in ambient temperature of 0. E0der C and relative humidity of 15,00%
		temperature of 0-50deg C and relative humidity of 15-90%
		26. The unit shall be capable of operating continuously in ambient temperature of 10, 40 deg C and relative humidity of 15, 00%
		of 10 -40 deg C and relative humidity of 15-90% 27. Should have local service facility .The service provider should have the
		necessary equipments recommended by the manufacturer to carry out
		preventive maintenance test as per guidelines provided in the
		preventive mantenance test as per guidennes provided in the

No.	Name of Equipment	Specifications Required for the Equipment to be purchased
		service/maintenance manual
		28. User/Technical/Maintenance manuals to be supplied in English.
		29. Certificate of calibration and inspection.
		30. List of important spare parts and accessories with their part number and costing
		31. Log book with instruction for daily, weekly, monthly and quarterly maintenance checklist.
		32. The job description of the hospital technician and company service engineer should be clearly spelt out

<u>Schedule-C</u>

MULTIPARA MONITOR (8 Nos.)

No.	Name of Equipment	Specifications Required for the Equipment to be purchased
		 Basic parameters (ECG/heart rate, O2 saturation, NIBP & respiration) – in all monitors General :
		 The equipment should come with all standard accessories required to run all parameters, suitable for all patient categories, ie. infants, children and adolescents. Waveform display: at least 5 channels, user selectable. Digital display: Heart rate, respiratory rate, oxygen saturation, Non Invasive Blood Pressure.
		3. Individual Monitors :
		 Wall mountable and pivotable
		 Medical grade, TFT Flat screen, slim size, at least 19" display
		 Screen resolution at least 1280x1024 pixels
		 Clear bright color display with large character size
		 Viewing angle at least 90o
		 Adjustable contrast and brightness
		 Ability to zoom any parameters
		 Ability to adjust individual alarms
		 Ability to change color of the trace by user
		4. Parameters monitored :
		The following modules complete with their accessories:
		 Heart rate/ECG
		 Respiration
		 Oxygen saturation
		Noninvasive Blood pressure
		5. Heart rate/ECG:
		• At least 3-lead selectable ECG
		 Built in arrhythmia monitoring in all leads
		 Inbuilt ST segment analysis and arrhythmia detection facility Diale for Second and the second s
		 Display of 2 ECG leads simultaneously at a time
		 Heart rate range 30-300 bpm A surgery + 5 brunch
		 Accuracy + 5 bpm Display around 12.5, 25 mm (and (man adjustable))
		 Display sweep speeds 12.5, 25 mm/sec (user adjustable) Assure size times user called table on to 8 seconds
		 Averaging time: user selectable up to 8 seconds

No.	Name of Equipment	Specifications Required for the Equipment to be purchased
		ECG amplitude user adjustable
		Defibrillator protected
		6. Respiratory rate
		 Measured by transthoracic impedance using the same ECG lead Dense (to 120 breachs(min)
		 Range 6 to 120 breaths/min Accuracy + 2 hpm
		recutacy + 2 opin
		 Display sweep speeds 6.25, 12.5 & 25 mm/sec (user adjustable) Averaging time: user selectable up to 8 seconds
		 Averaging time, user selectable up to 8 seconds User selectable apnea alarm time
		7. Oxygen Saturation
		 Dual wavelength LED pulse oximetry
		 Range 1 to100%
		 SpO2 accuracy : + 2 % (40-100% range)
		 Averaging time: user selectable up to 8 seconds
		 Plethysmographic waveform display
		8. Noninvasive Blood pressure :
		 Capable of measuring blood pressure in infants, children and adolescents.
		 Microprocessor software with unit in mmHg
		 Oscillometric technique
		 Manual, auto and time limited stat modes
		 User selectable automatic time intervals
		 Display systolic, diastolic and mean BP
		 Blood pressure range
		• Systolic : 30- 250 mm Hg
		Diastolic : 10-120 mm Hg
		• Mean: 20 – 100 mmHg
		 Pulse rate range : 20-300 bpm
		 Cuff : auto deflate with over pressure protection
		 Should automatically establish zero reference after each reading
		9. User selectable alarms
		 High and low heart rate
		 High and low respiratory rate
		 Apnea with adjustable time 5-20 seconds
		 High and low saturation
		 High and low SBP
		 High and low DBP
		 High and low MAP
		Probe failure
		 Poor signal
		 Power failure
		 Audio & visual alarms with message
		10. Trends
		 Memory storage : at least 72 hours
		 Data display interval : not more than 20 sec
		 Display range : last ¹/₂ hour to 72 hours
		 Graphical and tabular format of display of variables
		11. Power
		• 220/240 V
		• 50/60 Hz AC

No	Name of	Specifications Dequired for the Equipment to be purchased
No.	Name of Equipment	Specifications Required for the Equipment to be purchased
	Lyuipinent	
		- Deduced by the transformation of the base of the transformation
		 Rechargeable internal battery with a back up of at least 1 h Manually Quantum framework
		12. Manuals : Operator & service manuals
		13. Should be approved & certified by FDA (USA) and European CE
		14. Manufacturer should have ISO certification for quality standards
		15. Shall meet the safety requirements as per IEC 60601-2-27:1994—Medical electrical equipment—Part 2: Particular requirements for the safety of electrocardiographic monitoring equipment
		16. Availability of consumables for at least 10 years after date of installation
		17. Warranty and CMC would include the periodic calibration of all parameters strictly as per manufacturer's recommendations and any spares or standards required for that.
		 18. Onsite physical demonstration of the monitor with all the requested modules will be mandatory
		19. Essential Accessories for eight (08) monitors
		The following quantities are to be supplied with the initial order:
		ECG/Respiration
		• ECG patient cable : 16
		 ECG lead wires set (at least 3 leads) : 16 sets
		Disposable ECG electrodes for infants, pediatrics and adolescents:50 sets of
		infants and pediatrics each and 50 sets of adolescents .
		 Oxygen saturation
		 Patient extension cables: 16
		 Reusable wrap around probes: 24
		 Reusable Y shaped finger probes: 24
		NIBP
		 Patient extension cable – 16
		 Disposable NIBP cuff of size suitable for neonates (>2000g): 25 no.
		 Reusable cuffs of infant, pediatric and adult size- 2 each with each monitor
		20. Cost of consumables/accessories should be frozen for the period of warranty and CMC.
		21. The unit shall be capable of being stored continuously in ambient temperature of 0-
		50deg C and relative humidity of 15-90%
		22. The unit shall be capable of operating continuously in ambient temperature of 10 -50
		deg C and relative humidity of 15-90%
		23. Should have local service facility .The service provider should have the necessary
		equipments recommended by the manufacturer to carry out preventive maintenance test
		as per guidelines provided in the service/maintenance manual
		24. User/Technical/Maintenance manuals to be supplied in English.
		25. Certificate of calibration and inspection.
		26. List of important spare parts and accessories with their part number and costing
		27. Log book with instruction for daily, weekly, monthly and quarterly maintenance
		checklist.
		28. The job description of the hospital technician and company service engineer should be
		clearly spelt out.

MANUFACTURER'S / PRINCIPAL'S AUTHORIZATION FORM

(Clause 13 (C) of the tender)

То

The Administrative Officer, All India Institute of Medical Sciences Raipur

Dear Sir,

TENDER: ______.

we, who are established reputable manufacturers of and having factories hereby at and_ authorize Messrs. (name and address of agents) to bid, negotiate the with against and conclude contract you Tender goods manufactured No. for the above by individual other us. No company or firm or than Messrs. are authorized to bid, negotiate and conclude the contract in regard to this business against this specific tender.

We hereby extend our full guarantee and warranty as per the conditions of tender for the goods offered for supply against this tender by the above firm.

The authorization is valid up to ______

Yours faithfully,

(Name)

For and on behalf of Messrs. ______ (Name of manufacturers)/Principal.